

**Disc Brake With Thrust Piece**

The present invention concerns a pneumatically and/or electromotively actuatable disc brake according to the preamble of claim 1.

Disc brakes are known, e.g. as shift caliper disc brakes, swivel caliper disc brakes, or fixed caliper disc brakes.

Shift caliper disc brakes require a fixed-axis component, which carries the brake linings effective at one side of the disc brake, and which absorbs its peripheral force when the disc brake is activated, and also holds the caliper displaceably lodged in parallel to the axis of the vehicle. The relative movement, which the caliper performs against the fixed-axis component, can be divided into power stroke and tear stroke.

To balance the wear of the brake lining and/or disc brake, at least one adjustment device is arranged in the caliper, which acts upon the brake lining by means of one or two thrust pieces that are displaceable essentially axially to the disc brake, in order to adjust the distance between the brake lining and the brake disc.

If separate adjustment devices are arranged on both sides of the brake disc, it is merely necessary to align the displacement path of the brake disc in such a way that the release clearance can be overcome and the elastic deformation of the brake lining and the caliper, in other words the power stroke, can be balanced out (see e.g. PCT/EP01/09366).

The adjustment devices provided on both sides of the disc brake consist e.g. of adjustment sleeves, which, as adjustment elements of an electric motor or another mechanical device are pivotable via a gear; these adjustment sleeves consist of an inside thread, into which a bolt-like member of the respectively thereto arranged thrust piece is screwed, so that with appropriate rotation, a relative axial movement is provided between the adjustment sleeves and the thrust pieces. Also known is a reverse arrangement, in

**BEST AVAILABLE COPY**

which the thrust pieces have a sleeve-like porter, which is pivotable on a bolt that forms the adjustment element.

The brake lining material is directly connected to the lining support, which in turn is either connected with the thrust piece, or rests against the lining support "loosely" without connection.

From DE 42 30 005 A1 a disc brake with a shift caliper is known, in which on each side of the disc brake two thrust pieces arranged next to one another each act on a lining support of a brake lining, which is equipped with a lining support material.

A disadvantage of these known constructions lies in the fact that the frictional heat that is generated during a braking action is conducted through all components of the adjustment device without any blockage, whereby the downstream functional elements are exposed to a special stress, which reduces the service life. This is especially of concern when electric motors are employed as drive units for the adjustment devices.

Since disc brakes, which are utilized in utility vehicles, are subjected to the highest stresses, this issue is of particular significance, especially in terms of economy, since a shortened service life, and consequently the replacement of the corresponding functional elements, entails not only repair costs, but also costs that arise from the necessary outage time of the utility vehicle.

From DE 39 19 179 a disc brake is known, in which, at the side of the brake lining that faces the thrust piece, an insulating board is mounted at the lining support, which reduces the flow of heat between the brake lining and the thrust piece. Since a high generation of heat at the brake disc and the brake linings is obtained with braking, the insulating board protects the inside of the caliper - that is the clamping unit and the adjustment device - against overheating. The problem can be minimized by means of this solution.

It is also necessary to keep the thrust pieces and the adjustment elements torsion-resistant, in order to achieve, in conjunction with stationary, yet pivotable corresponding elements, such as adjustment sleeves with an inside thread, in which the adjustment elements are provided as a thread spindle, an axial movement of the thrust pieces.

The present invention is therefore based on the objective of further developing a disc brake of the generic form such that with constructively minor measures, on the one hand during braking actions a reduced heat conduction into the inside of the caliper, and/or a constructively simple method for securing torsion-resistance of the adjustment elements and their corresponding elements is achieved.

This objective is attained with a brake disc that has the characteristics of claim 1.

Accordingly, the two adjustment elements of the at least one single adjustment device, are attached torsion-resistently in their area facing their respective brake lining, on a common connection plate; and/or at the connection plate, and/or at the thrust piece on the side facing the respective brake lining a one-part or multi-part heat-insulating layer(s) is/are attached at least in sections.

As compared with the state of the art, this connection plate in its function as securing torsion-resistance offers not only substantial advantages as far as production and assembly are concerned, due to its simple construction, but also functional advantages, since the connection plate always remains at the same position on the thrust pieces, i.e. the connection plate moves according to the axial displacement of the thrust pieces along with them.

Thereby, in addition to the constructively uncomplicated securing of torsion-resistance of the thrust pieces, a protection of the downstream functional components from the effects of heat is also effectively enabled via simple means; this is achieved on the one hand by the connection plate itself, and on the other hand by the layer on this plate, or at the thrust piece.

Thereby, strain caused by the excessive heating of the parts arranged in the inside of the caliper, or an impairment of their ability to function during continuous or frequent heating with the resulting issues described in the state of the art, are prevented.

Preferably, the connection plate is realized as a thermal shield, which is dimensioned in such a way that it covers the opening of an installation space in the caliper, in which the adjustment device is placed, covered to a large extent. In addition, the opening may be closed by means of a further cover plate, which is screwed in at the opening of the caliper, and therefore is not axially displaceable, and has breakthroughs for the thrust elements.

It is extremely advantageous if the heat-insulating layer is realized in one part or several parts, and is directly mounted onto the connection plate. The layer may consist of one or two ceramic plates, which protrude over the thrust piece beyond its largest diameter dimension, wherein this ceramic plate is mounted on the connection plate, which is connected form flush and/or force flush with the thrust pieces, and which functions as heat protection, and as a device for securing torsion-resistance for the two thrust pieces of an adjustment device.

According to a further preferred modification, a thrust piece that forms the thrust piece plate is positioned upon the connection plate, and supports the heat-insulating layer. It is also conceivable, however, to place a ceramic layer on the thrust piece plate. In this manner, the connection plate is clamped by the thrust piece plate.

Preferably, the thrust piece plate is held at the connection plate form flush in an axial direction and torsion-resistant.

Especially preferably, the thrust piece plate has recesses that face the connection plate, which are contact-free in the material.

According to a further advantageous modification, the connection plate in turn has protuberances in the connection area with the adjustment elements facing the brake lining, in which protuberances the adjustment elements are appointed in a simple manner axially, and torsion-resistantly.

It is thus of further advantage for the cylinder-shaped protuberance to have stop notches realized in its surface area, which are realized in the interior of the protuberance in the form of catch grooves, and which on the outside correspond to catch grooves on the thrust piece plate, and on the inside correspond to noses of the adjustment element, and thus especially allow for a simple assembly of these constructional elements.

According to a further modification, the area embedded in the protuberance of the adjustment element has on its surface side slots that break through the material. In order to achieve optimized heat insulation, the thrust piece plate may also be provided with breakthroughs, which are, for example, arranged next to one another in a radial direction, and which effect heat insulation in this area. In each of these cases, the thrust piece plate and the thrust piece are connected torsion-resistantly to the connection plate.

In addition, expansion bellows may be connected at the connection plate, covering the respective adjustment elements as protection.

According to a further – also to be considered separately – modification of the invention, the thrust pieces and the lining support are each connected to one another in such a way that – continuously and in a simple way – a retraction of the brake lining is guaranteed, when the adjustment elements are turned back and when the brake is released.

With respect to the construction, it is of special advantage if at the thrust piece, or at a component of the adjustment element connected with this, one or several plate springs are arranged, which undercut a rod in a recess of the lining support. As an alternative, one or more plate springs may be arranged at the lining support, which undercut the thrust piece or a component of the adjustment element connected to it.

Further advantageous embodiments of the invention are characterized in the sub-claims.

Exemplary embodiments of the invention are described in the following by way of the enclosed drawings.

Whereby is shown in

- Figure 1        a schematic illustration of the disc brake in a sectional side view;
- Figure 2        a partial section of a top view of the disc brake;
- Figure 3        a detail of the disc brake in a frontal view;
- Figure 4        the detail according to Figure 3 in a plan view;
- Figure 5        a cross-section through the detail according to Figure 3 along the line V-V in Figure 3;
- Figure 6        a further exemplary embodiment of a detail of a disc brake of the invention in an exploded view;
- Figure 7        a cross-section through the detail according to Figure 6 along the line VII-VII in Figure 6;
- Figure 8        a cross-section through a caliper section of a further disc brake.

In Figures 1 and 2 a pneumatically actuatable disc brake is shown, which has a caliper 1 realized as a fixed caliper, which consists of a brake disc 2 in its upper peripheral area. Conceivable, yet not shown, is also an electromotive actuation of the disc brake.

On both sides of the disc brake 2, various brake linings 3, 4 are arranged in its direction, and away from it, i.e. vertical to its plane, which, as is customary, consist of a lining support 3a, 4a, and lining material 3b, 4b applied thereon.

The caliper 1 in Figure 1 in the right lower section 21, which extends in the direction of a not shown axletree, is attached at an axle flange 22 of the disc brake.

Here, the disc brake 2 is embodied by way of example as a disc brake, which is displaceable relative to the caliper 1 on the axletree by the amount of the power stroke to be overcome during braking actions. As an alternative or in addition, the caliper 1 may also be realized displaceably or pivotably. It is furthermore conceivable for the caliper 1 and/or the disc brake 2 to be realized as elastically deformable in one part of the path of the power stroke.

Since a relative movability is given between the caliper 1 and the disc brake 2, which essentially corresponds to the amount of the power stroke, an adjustment system 5, 6 is provided. This consists of adjustment devices 7, 8 on both sides of the disc brake 2, to balance the release clearance or the brake lining wear resulting from the braking action.

The adjustment devices 7, 8 consist here on each side of the disc brake 2, by way of example, of at least one or more, preferably two, adjustment sleeves 19, 20, in which bolt-like lugs 38, 39 of thrust pieces 11, 12, functioning as adjustment elements 9, 10, are carried pivotably in such a way that a relative axial movability is given between the adjustment sleeves 19, 20 and the thrust pieces 11, 12.

Of course an inverse arrangement is conceivable as well, wherein the one- or multi-part thrust pieces 11, 12 have a sleeve-like lug 40, 41, in which a bolt, onto which a gear of the adjustment drive acts like an electric motor M, is carried pivotably. Such a sleeve-like realization of the adjustment elements 9, 10 can be seen in Figures 5 and 7.

The adjustment device 7 shown in Figure 1 on the right side, is supported by a pivot lever 23 arranged next to it and pertaining to the clamping device, which in its upper section is actuable by a piston rod 24 of a brake cylinder 25, and which in its lower section is borne, for example, by not shown ball elements or by another bearing at the caliper, and which on its side that faces away from the caliper is borne at the adjustment sleeve 19 directly or via intermediate elements such as balls and/or other intermediate pieces.

The adjustment sleeve 20 arranged at the side of the brake disc 2 opposite the pivot lever 23, however, is directly supported by the inside of the caliper.

As can be seen, especially when Figures 1 and 3 are working together, the two adjustment elements 9, 10, which pertain to the respective adjustment system 5 or 6, which extend parallel and with a spacing, and which are movable in the direction of the brake disc 2 axially back and forth, are connected to one another on both sides of the brake disc by means of a yoke-like connection plate 15 or 16, which may also be realized as sheet metal, in such a way that they are held torsion-resistantly relative to one another.

On their side that faces the disc brake, the connection plates 15, 16 are each directly or indirectly layered with a continuous, or only locally applied – e.g. realized in a circular form – heat-insulating layer 13, 14, which prevents the frictional heat that is created by the braking action from being conducted to further, downstream functional components. The connection plates 15 and 16, working in conjunction with the heat-insulating layers 13, 14, e.g. made of ceramic, function here as thrust pieces 11, 12.

The connection plates 15, 16 serve, apart from the support and securing of the torsion-resistance of the adjustment devices 7, 8, also as a protective shield for the functional components arranged behind them (e.g. the electric motor M) against heat radiation, since they completely or largely close openings realized in the caliper toward the disc brake, as is schematically indicated in Figure 1.



By the torsion-resistant attachment of the thrust pieces 11, 12, and therefore of the adjustment elements 9,10, their joint axial displacement, and therefore a displacement of the brake linings 3, 4 is made possible, whereby in the realization of the adjustment elements 9, 10 the adjustment sleeve 19, 20 rotates as a threaded bolt, whereas if the adjustment elements 9, 10 are realized as a threaded sleeve, the correspondingly realized bolt can rotate therein.

In Figures 3-5 an exemplary embodiment of the connection plate 15 with a thereto connected or positioned heat-insulating layer, in either case in two parts, is shown. The layer 13 forms the actual thrust contact surface toward the brake lining.

As is especially represented in Figure 3, the connection plate 15 is formed and dimensioned in such a way that it largely covers the front side of a seat of the caliper 1 (Figure 1), in which the respective adjustment system 5, 6 is positioned.

In this exemplary embodiment according to Figures 3 and 5, the heat-insulating layer 13 consists of two plates or discs, for example made of ceramic, which are embedded in the connection plate 15, and are attached therein.

To protect against dirt and debris, the thrust piece 11 is covered up to an area that partially covers the adjustment element 9, by means of an expansion bellows 17, which, on the side facing away from the heat-insulating layer 13 of the connection plate 15, is attached thereto.

The expansion bellows 17 is hereby attached at its side that faces the connection plate 15 to an inner collar 45 on the thrust element 9, and to an outer collar 46 on the connection plate 15, which allows for the assembly, and the balancing out of radial movement between these components.

A further exemplary embodiment of the invention is shown in Figures 6 and 7.

Herein, the rather sheet metal-like realized connection plate 15 has a crimp folding 34 in its center area, which balances out longitudinal changes caused by heat.

It is further shown that the connection plate 15 for seating the thrust piece plates 38 has a protuberance 28 in each case, which is provided with a closed bottom section, in which the facing terminal front area of the thrust piece plate 38 is embedded.

This protuberance 28 has formed areas that form at the surface of the protuberance 28 radially arranged stop notches 29, which to the inside, due to the given shape, form a catch groove, into which noses 31 of the adjustment element 9 engage, whereby the stated securing of torsion-resistance is produced.

In the terminal area of the adjustment elements 9, 10 that faces the protuberance 28, radially extending slots 32 are provided on the surface area, which form both a heat insulation and breakthroughs 33, which are provided at a thereto formed collar 35 of the thrust piece 11, and which extend radially.

Figure 7 shows that the terminal area of the thrust piece 11 embedded in the protuberance has an undercutting 36 on its surface side. For the axial fixation of the thrust piece 11, a thrust piece plate 26 is pressed onto the protuberance 28, by means of which the surface area of the protuberance 28 is pressed into the undercutting 36 of the adjustment element 9, wherein a corresponding formation of the thrust piece plate 26 rests against the surface of the protuberance 28 in this section.

The thrust piece plate 26 consists of radially extending recesses 27, which also serve as heat insulation, or an interruption of the heat transmission.

In the side walls of a center opening 37 of the thrust piece plate 26, catch grooves 30 are mounted, which correspond to the stop notches 29 of the protuberance 28, thereby forming a securing for torsion-resistance of the thrust piece plate 26.

Figure 7 shows that the heat-insulating layer 13 is attached onto the circular area of the thrust piece plate 26, namely on the side that faces the brake lining 3, 4.

Figure 8 makes clear that at the thrust piece 11, 12, or at another component at the adjustment element 9,10, on both sides of the disc brake 2, one or more plate springs 42 are joined, each undercutting a rod 43 in a recess 44 of the lining support. Thereby the thrust pieces 11, 12 are respectively connected to the lining supports 3b, 4b in such a way that a retraction of the brake linings 3, 4 is guaranteed when the adjustment elements 9, 10 are turned back, and when the brake is released. The arrangement may also be reversed, i.e., so that the spring is formed onto the lining support, and engages into a recess at the adjustment element 9,10, or thrust piece 11, 12. The principle from Figure 8 may also be utilized in the modifications in Figures 1 through 7.

Legend

- 1 Caliper
- 2 Brake disc
- 3 Brake lining
- 3a Lining support
- 3b Lining material
- 4 Brake lining
- 4a Lining support
- 4b Lining material
- 5 Adjustment system
- 6 Adjustment system
- 7 Adjustment device
- 8 Adjustment device
- 9 Adjustment element
- 10 Adjustment element
- 11 Thrust piece
- 12 Thrust piece
- 13 Heat-insulating layer
- 14 Heat-insulating layer
- 15 Plate
- 16 Plate
- 17 Expansion bellows
- 18 Expansion bellows
- 19 Adjustment sleeve
- 20 Adjustment sleeve
- 21 Section
- 22 Axis flange
- 23 Pivot lever
- 24 Piston rod

25	Brake cylinder
26	Thrust piece plate
27	Recess
28	Protuberance
29	Stop notch
30	Catch groove
31	Nose
32	Slot
33	Breakthrough
34	Crimp folding
35	Collar
36	Undercutting
37	Center opening
38	Bolt-like lug
39	Bolt-like lug
40	Sleeve-like lug
41	Sleeve-like lug
42	Plate springs
43	Rod
44	Recess
45	Collar
46	Collar
M	Electric motor

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**